

# **CONCRETE SEALER**

## **DESCRIPTION/FEATURES:**

 Aqua Mix Concrete Sealer is a natural-look, below-surface sealer designed to resist stains.

#### **USES:**

- Recommended for use on:
  - Concrete
  - Masonry
  - Unpolish Natural Stone
- Equally effective for interior and exterior applications

#### **AVAILABLE SIZES:**

 Concrete Sealer is available in gallon, 5-gallon pail, and 55-gallon drum sizes

#### **COVERAGE:**

Approximately 400 to 800 sq. ft. (30 <sup>m2</sup> to 95 m<sup>2</sup>) per coat per gallon (3.875 L), depending on type of tile, porosity and texture of surface, temperature, humidity and method of application

#### **EXPECTED WEAR:**

 Will vary depending on hardness and texture of surface, type of area, surface wear, frequency and type of maintenance products used, the expected wear is up to 3 years. Extreme weather conditions, harsh cleaning methods and high-alkaline or solventbased cleaners will affect wear.

## METHOD OF APPLICATION:

- Read entire label before using
- TEST A SMALL AREA, according to application instructions, with a 24-hour cure time to determine desired results. Test for stain repellency using likely contaminants.
- On newly poured concrete, sealer can be applied 14 days after initial cure.
- Surface must be clean, dry and free of existing sealers and coatings and curing agents.
- Apply 1 to 3 coats using a dense sponge applicator, paint roller, sprayer or brush. Avoid overlapping, puddling and rundown.
- Completely wipe surface dry 3 to 5 minutes after application using cotton or paper towels.

## **CURE TIME:**

- Allow 1-hour drying time between coats
- Ready for surface traffic in 2 hours
- Keep area dry for at least 12 hours
- Achieves a full cure in 24 hours
- After 2 hours conduct a test to determine if surface is completely sealed by applying water droplets to the surface. If water is absorbed, apply an <u>additional</u> coat. Wait 2 hours and repeat the test.

## **LIMITATIONS:**

- $\bullet$  During application, surface temperature should be between  $50^{\circ}\,F$  and  $80^{\circ}\,F$  (10° C and 27° C)
- Do not allow sealer to come in contact with any non recommended surface

#### HANDLING AND STORAGE:

- · Close container after each use
- · Store in original container only
- Store and use in temperatures between  $50^{\circ}$  F and  $80^{\circ}$  F ( $10^{\circ}$  C and  $27^{\circ}$  C)
- Protect unused, stored product from freezing

## **CAUTION:**

- KEEP OUT OF REACH OF CHILDREN
- Eye and skin irritant
- · May be harmful if swallowed
- Contains siliconates
- Do not take internally
- Rubber gloves and eye protection should be worn during application
- IF INGESTED: Do not induce vomiting. Drink 1 to 2 glasses of water. Seek immediate medical attention.
- EYE CONTACT: Flush thoroughly with water. Seek immediate medical attention.
- SKIN CONTACT: Flush with water

©2001 1101