

## PRO-SOLV 10 STONE SEALER

### DESCRIPTION/FEATURES:

- AQUA MIX PRO-SOLV 10 STONE SEALER is a premium, no-sheen, natural-look, solvent-based penetrating sealer formulated to provide excellent stain protection, especially in food preparation and serving areas. May also be used as a pre-grouting sealer over clean stone surfaces a minimum of 6 hours prior to grouting. Allows moisture vapor transmission.

### USES:

- Recommended for use on marble, granite and other natural stones where a natural look is desired
- Also excellent on porous tile and grout
- Equally effective for interior and exterior applications

### AVAILABLE SIZES:

- Pro-Solv 10 Stone Sealer is available in pint, quart, gallon, 5-gallon pail, and 55-gallon drum sizes

### COVERAGE:

- Approximately 400 to 1,500 sq. ft. (35 m<sup>2</sup> to 140 m<sup>2</sup>) per coat per gallon (3.875 L), depending on type of stone, porosity and texture of surface, temperature, humidity and method of application

### EXPECTED WEAR:

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency and type of maintenance products used. The expected wear is **up to 10 years**. Extreme weather conditions, harsh cleaning methods and high-alkaline or solvent-based cleaners will affect wear.

### METHOD OF APPLICATION:

- **Read entire label before using**
- **TEST A SMALL AREA** according to application instructions, with a 24-hour cure time to determine desired results. Test for stain repellency using likely contaminants.
- For new installations, sealer can be applied 48 hours after grouting
- Surface must be clean, dry and free of existing sealers or coatings
- Apply 1 to 3 coats using an applicator, natural-bristle brush, paint pad, white cotton towels or solvent-resistant sprayer. One coat should be sufficient for most dense surfaces.
- Using absorbent white cotton towels, polish dry any sealer remaining on the surface within 3 to 5 minutes of application

### CURE TIME:

- Allow 30 minutes drying time between coats
- After two 2 hours conduct a test to determine if surface is completely sealed by applying water droplets to the surface. If water is absorbed, apply an additional coat. Wait 2 hours and repeat the test.
- Ready for surface traffic in 2 hours
- Keep area dry for 12 hours
- Achieves a full cure in 24 hours

### MAINTENANCE:

- Aqua Mix Stone Cleaner is recommended for routine cleaning

### LIMITATIONS:

- Do not allow sealer to come in contact with any non-recommended surface
- May slightly lighten or darken some stone surfaces
- Sealer will not prevent surface wear or etching from acids or caustic chemicals

### HANDLING AND STORAGE:

- Close container after each use
- Store in original container only
- Store and use in temperatures between 40° F and 90° F (4° C and 38° C)
- Unused, stored product is freeze-thaw stable
- Dispose of residue or any unused leftover product in accordance with applicable federal, state and local regulations

### DANGER:

- **KEEP OUT OF REACH OF CHILDREN**
- Combustible
- Contains petroleum distillates
- Use in well ventilated areas
- Avoid prolonged skin contact
- **Wear organic vapor respirator, solvent-resistant gloves, safety goggles and protective clothing**
- **IF INGESTED:** Do not induce vomiting. Drink 1 to 2 glasses of water. Call physician immediately.
- **EYE CONTACT:** Flush with water. If irritation persists, seek medical attention.
- **SKIN CONTACT:** Wash immediately with soap and water. If irritation persists, seek medical attention.
- **INHALATION:** Relocate to fresh air. If symptoms persist, seek medical attention.

**AQUA MIX INC.**

P.O. BOX 4127, SANTA FE SPRINGS, CA 90670

Technical Assistance: 800-366-6877

FAX: (562) 944-8873