



Master
Resources Co., Ltd.

บริษัท มาสเตอร์ รีซอร์สเซส จำกัด

Technical Bulletin

Master CSS Plasma is a Nano state of the art technology,
Evolution single step, user friendly system.
Exactitude mineral formulation reducing the surface oxide crystal,
Treating and hardening all types of calcareous composition floor surfaces into a highly
durable glossy and natural finishes.
Maximize the floors luster, excellence shine and durability.
Without losing the slip resistance characteristics
Excellence on Marble, Limestone, Terrazzo and natural stone.

Shake Well Before Use.

COVERAGE:

Approximately 600 – 800 sq. ft. (60 -80 m²) per 1 liter

METHOD OF APPLICATION:

- Read entire label before using
- TEST A SMALL AREA, according to application instructions to determine desired results
- Ensure surface is clean and dry.
- Spray / apply CSS Plasma onto a manageable area of approximately 5 to 10 sq. ft. (0.5 m² to 1 m²)
- Using a synthetic fiber white pad, work the area in a side-to-side motion with a 175 to 300 RPM floor machine be sure to overlap the sections to achieve an even polish.
- Reapply / continue until the required enhance polish result has been achieved
- Apply or spray CSS liquid as require for higher gloss result as needed depending on surface traffic and consistency of routine maintenance program

CAUTION:

- KEEP OUT OF REACH OF CHILDREN
- INHALATION: Move to fresh air
- IF INGESTED:

Do not induce vomiting. Drink 1 to 2 glasses of water.

Seek immediate medical attention.

- EYE CONTACT: Flush thoroughly with water for 15 minutes.

If irritation persists, seek medical attention.

- SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing