

Stone Gard Premium

DESCRIPTION:

• **Master** Stone Gard Premium New Formulation, is an natural-look, below-surface sealer designed to resist stains. Allows moisture vapor transmission. Repel all water-based fluids effectively from entering into the porous stone, does not form a coating. Sealer's performances will not affected by exposure to ultraviolet (UV) rays.

Tested on

Adhesion Strength	ASTM D 4541 :02
Chemical Resistance	ASTMD 1308:02(07)
Water Absorption,	
Breathing	SS-W-110C: 1972
Anti-Efflorescence	

USES:

• Equally effective for interior and exterior applications on marble, limestone, travertine, granite, terrazzo, grout and cementitious floor.

Expected wear • Will vary depending on hardness and texture of surface, type of area, surface wear, frequency and type of maintenance products used, the expected wear is up to 3 years. Extreme weather conditions, harsh cleaning methods and high-alkaline or solvent-based cleaners will affect wear

COVERAGE:

• Approximately 300 to 100 sq. ft. (30 m2 to 90 m2) per coat per gallon (3.875 L), depending on type of tile, porosity and texture of surface, temperature, humidity and method of application

MAINTENANCE:

• Master Stone Cleaner are recommended for routine cleaning

Ordering information:

AVAILABLE SIZES: Package

• Master Stone Gard are available in US gallon (3785ml)
Carton: 4 X 1 us gallon
www.master.co.th

METHOD OF APPLICATION: SHAKE WELL

• Read entire label before using

- **TEST A SMALL AREA** with a 24-hour cure times to determine the ease of application and desired results. Test for stain repellency using likely contaminants.
- Wash the top surface of the stone with [Master Stone Cleaner](#) (recommended) to remove all dust, dirt and soils before sealer application.
- To give effective protection on porous stone; allow the first coat of sealer to dry in the interior of the stone for at least 2 to 6 hours before applying a second application of sealer.
- Wipe or buff off any excess sealer almost immediately after each sealer application.
- Do not allow excessive sealer to dry on the surface; especially a polished marble and granite surface.
- Ready to surface traffic 20 minutes, Full cure 48 hours upon sealer application.
- Generally one coat is sufficient for polished surface stone and two (2) or more coat of penetrating sealer shall depend on the porosity of the stone. Usually limestone & rough texture stone require 2 and more application of sealer.

LIMITATIONS:

• Do not allow product to come in contact with any non recommended surface

HANDLING AND STORAGE:

- Close container after each use
- Store in original container only
- Unused, stored product is freeze-thaw stable

CAUTION:

- **KEEP OUT OF REACH OF CHILDREN**
- Eye protection and rubber gloves should be worn during application
- **IF INGESTED:** Do not induce vomiting. Drink 1 to 2 glasses of water. Seek immediate medical attention.
- **EYE CONTACT:** Flush with large amounts of with water. If irritation persists, seek medical attention.
- **SKIN CONTACT:** Wash with soap and water. If irritation persists, seek medical attention.

MASTER REFINISHING SDN BHD

Customer Support

Malaysia: +607 3511200 - +6012 7018890 – m_shchin@yahoo.com

Thailand: (66)02- 791-3845 - 086-068-2-333 - tstan@truemail.co.th

Middle East: +966 05680 61137 - +2010 1618 125 - mastermiddleeast@live.com