

Stone Enhancer

DESCRIPTION:

Master STONE ENHANCER is an excellent, no-sheen, enhanced-look, penetrating sealer formulated to darken and highlight the character and beauty of unsealed natural stone. It rejuvenates the color and improves the appearance of worn and weathered stone. Allows moisture-vapor transmission. It also effectively seals and darkens the color of grout joints.

• EXPECTED WEAR:

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used.
- The expected wear is up to 3-5 years.
- Exterior applications may require more frequent reapplications.
- Weather conditions, harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners will affect wear.

USES:

- Compress and natural stone such as honed or textured marble, granite, slate, limestone, travertine, quartzite, and sandstone.
- Effective for interior and exterior applications.

COVERAGE:

Approximately 500 to 1,500 sq. ft. (46 m² to 139 m²) per coat per gallon (3.785 L), depending on type of stone, porosity and texture of surface, temperature, humidity, and method of application.

TEST A SMALL AREA:

According to application instructions with a 24-hour cure time to determine desired results. Test for stain repellency using likely contaminants. Once enhanced, stone cannot be restored to original color appearance.

MAINTENANCE:

- Master Stone Cleaner is recommended for ongoing maintenance because many harsh (high-alkaline) cleaners may remove or dull the finish.

Ordering information:

Package: 1 Gallon Bottle (3.785 lit.)

Minimum: one carton/ 4 gallons

Method of application:

- 1) Read entire label before using.
- 2) For new installations, sealer can be applied as soon as 48 hours after grouting.
- 3) Surface must be clean, dry, and free of existing sealers or coatings.
- 4) Apply using a sponge, cotton towel,
NOTE: Be sure any sealer that does not penetrate surface is polished dry off surface within 5 minutes of each application using absorbent paper or cotton towels. If non-polished surfaces are left shiny after application, surfaces must be wiped dry as this indicates surface residue remains.
- 5) If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats. Remove surface residue after each application.
- 6) Ready for surface traffic in 12 hours after final coat. Keep dry for 12 hours. Achieves full cure in 48 hours. Some highly porous surfaces may require an additional coat after full cure.

LIMITATIONS:

- Do not allow sealer to come in contact with any non-recommended surface as product is not completely removable.
- Sealers and finishes should not be used before or after use of Master Stone Enhancer.
- If Master Stone Enhancer is not WIPED COMPLETELY DRY within 5 minutes, a residue may form.

Always try a small test area to ensure results. If results are not satisfactory, call technical services for additional options.

- Keep floor surfaces dry and clean to reduce possibility of slip-fall accidents.
- Routine pressure-washing will affect expected wear.
- Sealer will not prevent surface wear or etching from acids or caustic chemicals.

HANDLING AND STORAGE:

- Close container tightly after each use.
- Store in original container only. Store and use in temperatures between 40 °F - 90 °F (4 °C - 32 °C).
- Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements.

MASTER RESOURCES CO., LTD

Customer Support

Malaysia: +607 3511200 - +6012 7018890 – m_shchin@yahoo.com

Thailand: (66)02- 791-3845 - 086-068-2-333 - tstan@truemail.co.th

Middle East: +966 05680 61137 - +2010 1618 125 - mastermiddleeast@live.com