

CSS Black BASC

DESCRIPTION:

• **Master CSS Black Basc** penetrating enhancing sealer formulated to darken and highlight the character and beauty of unsealed natural stone.

It provide **Chemical Resistance, Harden & resist surfaces traffic.**

It act as an bridge and improve gloss during polishing.

USES:

• Equally effective for interior and exterior applications dark color stones and Cementitious floor.

Expected wear • Will vary depending on hardness and texture of surface, type of area, surface wear, frequency and type of maintenance products used, the expected wear is up to 3 years. Extreme weather conditions, harsh cleaning methods and high-alkaline or solvent-based cleaners will affect wear

COVERAGE:

• Approximately 300 to 100 sq. ft. (30 m2 to 90 m2) per coat per gallon (3.875 L), depending on type of tile, porosity and texture of surface, temperature, humidity and method of application

Surface Polishing

CSSV Black

MAINTENANCE:

• Master Stone Cleaner are recommended for routine cleaning

Ordering information:

AVAILABLE SIZES: Package

• Master Stone Gard are available in US 1 liter and gallon (3785ml)

Carton: 12 X 1 Liter. 4 X 1 us gallon

www.master.co.th

www.cleangloabl.com

METHOD OF APPLICATION: SHAKE WELL

• Read entire label before using

- **TEST A SMALL AREA** with a 24-hour cure times to determine the ease of application and desired results.
- Wash the top surface of the stone with [Master Stone Cleaner](#) (recommended) to remove all dust, dirt and soils before **Master CSS Black Basc** application.
- To give effective on porous stone; application of allow the first coat of **Master CSS Black Basc** after the #800 grind. Let to dry. Second application of **Master CSS Black Basc** after the #1500 grade of grinding.
- Wipe or buff off any excess **Master CSS Black Basc** almost immediately after each sealer application.
- Do not allow excessive **Master CSS Black Basc** to dry on the surface; especially a polished dark color marble and granite surface.
- Ready to surface traffic 20 minutes,

LIMITATIONS:

• Do not allow product to come in contact with any non recommended surface

HANDLING AND STORAGE:

- Close container after each use
- Store in original container only
- Unused, stored product is freeze-thaw stable

CAUTION:

- **KEEP OUT OF REACH OF CHILDREN**
- Eye protection and rubber gloves should be worn during application
- **IF INGESTED:** Do not induce vomiting. Drink 1 to 2 glasses of water. Seek immediate medical attention.
- **EYE CONTACT:** Flush with large amounts of with water. If irritation persists, seek medical attention.
- **SKIN CONTACT:** Wash with soap and water. If irritation persists, seek medical attention.

MASTER REFINISHING SDN BHD

Customer Support

Malaysia: +607 3511200 - +6012 7018890 – m_shchin@yahoo.com

Thailand: (66)02- 791-3845 - 086-068-2-333 - tstan@truemail.co.th

Middle East: +966 05680 61137 - +2010 1618 125 - mastermiddleeast@live.com