

# CSS Clear Concept V

## Description:

Master CSS Clear Concept V double density mineral solids reinforced with a base of unique Lithium silicate and Micro Crystal Quartz formulation designed to effectively strengthen and shine on Most calcium based and agglomerate Quartz applicable surfaces.

It restores and enhances to a high gloss, it gives an added chemical resistance and preservation properties thus increasing surface traffic and contamination resistance.

Designed for interior and exterior uses, with anti-slippery properties.

## Uses

Recommended for use on:

- Effective on Soft Marble and Limestone
- Porcelain and Homogenous Tiles
- Cementitious surface
- Sandstones
- Other Agglomerate Stones

## Coverage:

**Initial treatment approximately:**

**500-600 sq. ft. (45-55 m2) per US Gal**

**Surface Maintenance: 800 - 1000 sq. ft. (80 - 100 m2) per 1 liter**

**TEST A SMALL AREA, according to application instructions to determine desired results.**

## Caution:

- KEEP OUT OF REACH OF CHILDREN.
- INHALATION: Move to fresh air.
- IF INGESTED: Do not induce vomiting. Drink 1 to 2 glasses of water. Seek immediate medical attention.
- EYE CONTACT: Flush thoroughly with water for 15 minutes. If irritation persists, seek medical attention.
- SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing.

## Method of application:

1. Read entire label before using.
2. TEST A SMALL AREA, according to application instructions to determine desired results.
3. Ensure surface is clean and dry.
4. Spray / apply Master CSS Top Up onto a manageable area of approximately 5 to 10 sq. ft. (0.5 m2 to 1 m2)
5. Using a synthetic fiber white. pink or brown pad, work the area in a side-to-side motion with a 175 to 300 RPM floor machine
6. Be sure to overlap the sections to achieve an even polish.
7. Reapply / continue until the required enhance polish result has been achieved
8. Repeat the process if higher gloss require, apply or spray CSS Top Up depending on surface traffic and consistency of routine maintenance program.

## Handling and storage:

- Close container tightly after each use.
- Store in original container only.
- Store and use between temperatures of 40 °F - 90 °F (4 °C - 32 °C).
- Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements.

## Maintenance:

Apply or spray CSS Top Up as require for higher gloss result as needed depending on surface traffic and consistency of routine maintenance program.

## Ordering information:

Package: 1kg or 4kg Gal  
one carton/ 4 X 4kg

[www.master.co.th](http://www.master.co.th)

[www.cleanglobal.com](http://www.cleanglobal.com)

**MASTER REFINISHING SYSTEMS (M) SDN BHD**

Customer Support

Malaysia: +607 3511200 - +6012 7018890 – m\_shchin@yahoo.com

Thailand: (66)02- 791-3845 - 086-068-2-333 - tstan@truemail.co.th

Middle East: +966 05680 61137 - +2010 1618 125 - mastermiddleeast@live.com