

CSS Top Up

Description:

Master CSS Top Up new special formulation, double density mineral solids reinforced with a base of unique silicate and Micro Crystal Quartz formulation designed to strengthen on calcium based and cementitious applicable surfaces.

It restores and enhances to a high gloss, it gives an added chemical resistance and preservation properties thus increasing surface traffic and contamination resistance.

Designed for interior and exterior uses, with anti-slippery properties.

Uses

Recommended for use on:

- Marble
- Terrazzo
- Cementitious surface
- Porcelain Tiles
- Other Compress Stone

Coverage:

Initial treatment approximately:

500-600 sq. ft. (45-55 m2) per US Gal

Surface Maintenance: 800 - 1000 sq. ft. (80 - 100 m2) per 1 liter

TEST A SMALL AREA, according to application instructions to determine desired results.

Caution:

- KEEP OUT OF REACH OF CHILDREN.
- INHALATION: Move to fresh air.
- IF INGESTED: Do not induce vomiting. Drink 1 to 2 glasses of water. Seek immediate medical attention.
- EYE CONTACT: Flush thoroughly with water for 15 minutes. If irritation persists, seek medical attention.
- SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing.

Method of application:

1. Read entire label before using.
2. TEST A SMALL AREA, according to application instructions to determine desired results.
3. Ensure surface is clean and dry.
4. Spray / apply Master CSS Top Up onto a manageable area of approximately 5 to 10 sq. ft. (0.5 m2 to 1 m2)
5. Using a synthetic fiber white. pink or brown pad, work the area in a side-to-side motion with a 175 to 300 RPM floor machine
6. Be sure to overlap the sections to achieve an even polish.
7. Reapply / continue until the required enhance polish result has been achieved
8. Repeat the process if higher gloss require , apply or spray CSS Top Up depending on surface traffic and consistency of routine maintenance program.

Handling and storage:

- Close container tightly after each use.
- Store in original container only.
- Store and use between temperatures of 40 °F - 90 °F (4 °C - 32 °C).
- Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements.

Maintenance:

Apply or spray CSS Top Up as require for higher gloss result as needed depending on surface traffic and consistency of routine maintenance program.

Ordering information:

Package: 1kg or 4kg Gal
one carton/ 4 X 4kg

www.master.co.th

www.cleanglobal.com

MASTER REFINISHING SYSTEMS (M) SDN BHD

Customer Support

Malaysia: +607 3511200 - +6012 7018890 – m_shchin@yahoo.com

Thailand: (66)02- 791-3845 - 086-068-2-333 - tstan@truemail.co.th

Middle East: +966 05680 61137 - +2010 1618 125 - mastermiddleeast@live.com